

PENNZOIL ULTRA PLATINUM™ SAE 0W-40 FULL SYNTHETIC MOTOR OIL - *Made With Natural Gas*

TECHNICAL DATA SHEET



When it comes to torturous driving conditions, trust the unbeatable engine protection* of Pennzoil Ultra Platinum™. That means you're getting unbeatable wear- and sludge-protection as well as unbeatable cleanliness. Our 20-year, 750,000-mile warranty** protects your engine and gives you the peace of mind to drive every mile as hard as you can, from your daily commute to sand dunes and mountain terrain. No matter the road, choose Pennzoil Ultra Platinum™.

*Based on Sequence IVA wear test; Sequence IIH oxidation and deposit test; and the Sequence VH sludge test.

**Up to 20 years or 750,000 miles, whichever comes first, if you exclusively use Pennzoil Ultra Platinum™ Full Synthetic motor oil. Your engine must have fewer than 125,000 miles and have been manufactured in the past 72 months. To maintain your warranty, change your vehicle's oil and oil filter at least as often as recommended by the vehicle manufacturer. Enrollment required. Keep your receipts. Other conditions apply. See pennzoil.com/warranty to enroll and for full details and terms.

PERFORMANCE, FEATURES & BENEFITS

Feel the difference of next level performance with Pennzoil Ultra Platinum™, motor oil designed to deliver unbeatable engine protection.

CLEANER ENGINE

Unsurpassed engine cleanliness.¹

PROTECTS HORSEPOWER

Helps protect engines from loss of power.

BETTER FUEL ECONOMY

Better Fuel Economy based on the latest industry standards.

UNSURPASSED WEAR PROTECTION

Provides unbeatable wear protection.²

EXCELLENT PERFORMANCE IN EXTREME TEMPERATURES

Provides faster low temperature oil flow and protects in extreme heat.

¹ Based on Sequence VH Sludge Test using SAE 5W-20.

² Based on Sequence IVA wear test using SAE 5W-30.

MAIN APPLICATIONS

SAE 0W-40 viscosity grade engine oils are commonly recommended for use in many new vehicles with modern engine technology for maximum fuel economy and performance.

Pennzoil Ultra Platinum™ can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Exceeds the requirements of the following industry and OEM specifications:

- API SP and all previous Categories
- Chrysler MS-A0921

To find the right Pennzoil® product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

PENNZOIL ULTRA PLATINUM™ SAE 0W-40 FULL SYNTHETIC MOTOR OIL - Made With Natural Gas

TYPICAL PHYSICAL CHARACTERISTICS

Properties			Method	PENNZOIL ULTRA PLATINUM™ SAE 0W-40 FULL SYNTHETIC
Viscosity Grade			SAE J300	0W-40
Service Category				SP
Density		kg/m³	ASTM D4052	841
Flash Point		°C	ASTM D93	206
Pour Point		°C	ASTM D97	-51
Kinematic Viscosity	@40°C	cSt	ASTM D445	74.9
Kinematic Viscosity	@100°C	cSt	ASTM D445	13.7
Viscosity Index			ASTM D2270	189
CCS Viscosity	@-35°C	cP	ASTM D5293	5 850
MRV Viscosity	@-40°C	cP	ASTM D4684	21 500

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

Pennzoil Ultra Platinum™ SAE 0W-40 Full Synthetic Motor Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or technical helpdesk.