

Product Data Sheet

Revised: 2025/09/10 (version 1.1)

**Selenia ULTRA CP/03****5W-30****Description and Applications**

Selenia ULTRA CP/03 5W-30 is a fully synthetic lubricant developed in collaboration with Stellantis Group for petrol and diesel engines that require products capable of minimizing ash deposits (sulphate ashes, phosphorus and sulphur).

Its specific formula meets the specifications of Stellantis for diesel and petrol cars and is backward compatible with PSA B71 2290 and PSA B71 2297 approvals.

Approvals, Specifications and Recommendations**Specifications:**

- ACEA C3

Performance Level:

- PSA B71 2290
- PSA B71 2297
- FPW 9.55535/03

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density at 15°C	ASTM D4052	g/cm ³	0.845
Viscosity at 100°C	ASTM D445	cSt	7.9
Viscosity Index	ASTM D 2270	-	177
Flash Point Cl. O. C.	ASTM D 92	°C	228
T.B.N.	ASTM D 2896	mgKOH/g	10.3
Pour Point	ASTM D5950	-°C	-54

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further details regarding storage, safe handling, and disposal of product, please refer to product SDS.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations,

[\[Open\]](#)

or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 71106

