

Product Data Sheet

Revised: 2025/05/15 (version 1.0)



PETRONAS Urania Urban DM 0W-30

Designed with StrongTech™ technology that is trusted to keep engines in excellent condition and extend their service life

I feel confident and trust that my commercial vehicle will perform reliably, no matter the conditions or load. Seeing my customers happy and satisfied makes me proud of what I've achieved

Description and Applications

PETRONAS Urania Urban DM 0W-30 is a fully synthetic engine oil, with fuel economy and extended service interval capabilities, formulated with StrongTech™ technology, that forms a uniquely strong fluid film to protect the engine, retain performance and keep commercial vehicles running and available for longer periods. This helps to reduce the total cost of ownership.

Mid SAPS oil, suitable for light commercial vehicles fitted with both gasoline and diesel engines equipped with after treatment exhaust system and emission control devices such as diesel particulate filters and catalytic converters, port fuel injection or direct fuel injection, multi-valves, turbochargers or superchargers operating under most severe conditions.

Enhance your vehicle's performance by pairing PETRONAS Urania with PETRONAS Tutela fluids

Benefits

Contributes to enhance your vehicle availability through:

- **Extended Engine Life** driven by exceptional thermal and oxidation stability under high temperature, providing viscosity stability and preventing formation of deposits and sludge to prolong oil life even under severe conditions
- **Superior Fuel Economy** capabilities for the entire service interval
- **Outstanding protection** with high anti-wear properties to protect engines in **start-stop conditions**
- **Enhanced protection to after treatment exhaust systems**
- **Effectively combats high concentration of soot build ups, critical to prevent loss of vehicle horsepower**
- **Improved lubrication during start-up** thanks to its exceptional low temperature viscosity
- **Optimal viscosity levels and lubrication during service life, to prevent unplanned breakdowns**

Approvals, Specifications and Recommendations

Specifications:

- ACEA C3

Performance Level:

- MB 229.51/229.52

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.843
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	12.2
Viscosity Index	ASTM D 2270	-	180
Flash Point COC	ASTM D 92	°C	230
TBN	ASTM D 2896	mgKOH/g	10.2
CCS at -35°C	ASTM D5293	mPa·s	6000
Pour Point	ASTM D 97	°C	-48

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water. For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.